





SUBHAM POLES PROJECTS PRIVATE LIMITED

STANDARD DIMENSION OF HIGH MAST POLE

TOTAL	SEGMENT DETAILS				ТОР	воттом	CIRCULAR BASE	PCD	SIZE OF	NO. OF	LIGHT FITTING
HEIGHT	NO	LENGTH	THICK	SIDES	IUP	BOTTOW	PLATE OD X THK	FCD	BOLT	BOLT	PROVISION
10000	2	5250	3,3	8	100	300	500X20	400	M24X750	6	os Future
12500	2	6500	3,3	12	150	340	540X20	440	M24X750	6	6
16000	2	8250	4,3	20	150	360	540X25	460	M30X850	8	8
16000	2	8250	4,3	20	150	410	570X25	490	M30X850	8	12
20000	2	10300	4,3	20	150	410	570X30	490	M30X850	8	9
20000	2	10300	4,3	20	150	460	670X30	590	M30X850	8	12
25000	3	8750	5,4,3	20	150	460	670X30	590	M30X850	12	12
25000	3	8750	5,4,3	20	150	460	690X30	590	M30X1200	12	16
30000	3	10300	5,4,4	20	150	610	840X36	750	M30X1200	12	18


INTRODUCTION

Higmast Poles are most efficient pole to lighten the area by minimal resistance. Subham Highmast Poles are manufactured by our in-house skilled engineers to deliver the best to our clients. Highmast Poles are best applied located where today's busiest roads and expressways intersect or at parking lots or truck or bus terminals, ports, industrial areas, etc. We are one of the leading manufacturers of Highmast poles alongside various others products in our portfolio. Customized options are also available as per clients various needs.



NOTES

- ► Highmast Poles Range From 10m To 30m
- ► All Dimension Are In Mm (if Not Mention)
- ► Highmast Is Hot Dip Galvanized After Fabrication
- ➤ We Do Manufacture All Type Of Mast As Per Client's Demand
- MIN 65 110 (APPX)



FEATURES

- ► Precise Light Control
- ► Choice Of Light Distributions
- ► Zero Upward Light Option
- ► Versatile Mounting Arrays
- ► Safe Dependable Raise And Lower System
- ▶ Remote Control Portable Power Tool
- ▶ Positive Fail-safe Latching

MATERIAL SPECIFICATION

- ▶ Mast & Pole Shaft: BS EN 10025 Or Equivalent To Be UTS-470
- To 630m PA & YST-355(min) owards ruture
- Base Plate: Is: 2062 To Be UTS-410 (min) & YST-240 (min)

 Foundation Bolts: Special High Tensile Ms Round Confirms

 To2062,E250 A. The Bolts Are Threaded By Threading Machine

 With The Help Of Cheser And Threading Head.
- ► Galvanization: Is: 4759/ISO 1461



ENLIGHTENED TOWARDS FUTURE

HIGH MAST POLE

CORPORATE OFFICE:

54, Ezra Street, 2nd Floor, Kolkata - 700 001

Landline No: 033 7134 0610 | Mobile: +91 96740 77384 / 98366 43333 | email: info@subhampole.com

UNIT-1:

75/5, Kathore Road, Badu Bazar, Madhyamgram, Kolkata - 700128 Mobile : +91 96740 77455 / 98755 82266 | email : info@subhampole.com

UNIT-2

Amta-Ranihati Road Before Amta Industrial Park Village & Post Office IslampurPolice Station Jagatvallavpur Howarh-711401 West Bengal | Phone: +91 96740 77455 / 98755 82266